



C12000 EWX

12000LB 12V/24V ELECTRIC WINCH

Huge 6.5hp Series wound motor delivers maximum pull in the toughest environments. Outstanding features includes high quality double sealed motor with brass fittings, heavy duty waterproof contactors, double sealed drum on maintenance free bearings, quiet, efficient full steel planetary gearing. Stainless steel roller fairlead and fittings as standard. Complete with heavy duty integrated wireless remote.



STANDARD ACCESSORIES

- 26m x 10.2mm steel cable
- 3m Remote Handset
- Heavy Duty Stainless Steel Fairlead
- Heavy Duty Battery Leads
- Isolation switch
- Stainless Steel Mounting hardware
- Built In Wireless remote
- 5/16 hook

OUTSTANDING FEATURES

- All Brass (no corrosion) Series Wound Motor
- Double Sealed Motor
- Sealed Waterproof Contactor
- Steel Contactor Cover for Added Protection
- Double Sealed Drum (Gearbox/Motor)
- Sealed 3 Stage Planetary Gears
- Stainless Steel 4 Way fairleads
- Integrated Wireless Remote

SPECIFICATION

RATED LINE PULL: 12 000lbs (5400kg)
MOTOR: 12v : 6.5hp / 4.6kw
GEARING: 230:1
BRAKING ACTION: Automatic in the drum
DRUM SIZE Dia x L: 63 x 223mm
CABLE Dia x L: 10.2mm x 26m
MOUNTING PATTERN: 254 x 114.3mm
DIMENSIONS: 580 x 160 x 219mm

TECHNICAL PERFORMANCE

Layer of wire rope	Line pull lbs (kg)
1	12000 (5443)
2	9563 (4338)
3	7948 (3606)
4	6800 (3085)

Line pull lbs (kg)	Line speed		Amp draw	
	ft/min	m/min	12v	24v
0	22.3	6.8	100	60
4000 (1814)	13.1	4.0	220	130
8000 (3629)	9.8	3.0	330	170
12000 (5443)	5.8	1.8	450	220